

SEAL Ex Wearable GPS Tracker

ATEX Rated LoRaWAN® connected GPS Tracker for Locating Personnel

The **SEAL Ex** is an ideal solution for tracking your personnel working remotely in the field in difficult RF environments requiring ATEX Zone 1 certification where combustible gases, vapors or dusts may be present. The rugged IP67 rated and ATEX Zone 1 certified sensor is designed for the most demanding installations, with an operating temperature range of -20 to +52 °C. SEAL Ex Provides up to 11 months of battery life. SEAL Ex is designed with fall and impact detection for enhanced worker safety. The SEAL Ex wearable Tracker seamlessly integrated with TEKTELIC's End IoT solution.



Technical and Functional System Specifications

General System Parameters

Operational Temperature	-20°C to +52°C
Protection Rating	IP67
Size without safety clip*	104 x 70 x 34 mm
Size with safety clip*	104 x 70 x 56 mm
Battery	2x AA Batteries
Battery Life	11 months

LoRa Parameters

RF Power	15 dBm
RF Sensitivity	-137dBm (SF12, 125kHz)
ISM Band	All Global ISM Bands
Antenna	Internal
LoRa Device Class	Class A

Regulatory Compliance

Safety	EN IEC 62368-1:2020
	IEC 62368-1
Regulatory	ETSI EN 300 220-1/2
	ETSI EN 301-489-1
ATEX Specification	EN IEC 60079-0:2018
	EN 60079-11:2012
ATEX Marking	<Ex> II 2G Ex ia IIC T4 Gb

Specifications are in progress and subject to change*

Key Features

»	Fall Detection
»	Elevation Detection
»	Optional Harness Detection
»	Precise GPS & Integrated BLE
»	GNSS Datalogging
»	ATEX Zone 1 Certification
»	Data Transmission over LoRaWAN®
»	Event-Based Startup
»	Geofencing Capabilities
»	Audio & Visual Alarms
»	11 Months Battery Life
»	Rugged IP67 Design

GNSS Features

Position Accuracy	5 m
TIFF (Time to First Fix)	Cold Start - 26 Seconds
	Hot Start - 1 Second
Sensitivity	-164 dBm tracking and navigation
	-160 dBm reacquisition
	-148 dBm cold start
	-157 dBm hot start